Playground » Climbing and balancing elements



www.zaidimuaiksteles-bonita.lt



Climbing wall LS301KW - brown

Product type LS-301KW-20

Basic information

Age category 3 - 15 years Minimum area 6 m x 5 m

Equipment measurements 2,67 m x 0,98 m x 2,42 m

Free fall height:

Load capacity:

Max. number of users:

Fall zone: EN 1177

Designation:

2,0 m

324 kg

mull, 30 m²

exterior

Designation: exterior
Availability of spare parts: supplied by the
Certificate of Compliance: ČSN EN 1176 - 1

Material

Wooden units - water-proof plywood Metal units - structural steel

Climbing holds - mix of silica sand and epoxy resin

Finish

Duplex powder coated with coat curing Hot-dip galvanizing

2.67m

6m

Description

The support structure of the climbing wall is made from structural steel, it is zinc coated which significantly prolongs the life of the play unit or duplex powder coated with coat curing according to RAL to prevent corrosion. The structure is fixed in a concrete bed. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. The climbing wall is made from water-proof plywood designed for external use. The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. All fastening material is galvanized or stainless steel.

Equipment

We offer three color variants of the support structure - red, blue and brown.