



## Slide with a ladder KZ100KW - brown (f.h. 1,5 m)

Product type KZ-100KW-15

### Basic information

Age category	2 - 15 years
Minimum area	4 m x 7,5 m
Equipment measurements	1 m x 3,72 m x 2,26 m
Free fall height:	1,5 m
Load capacity:	270 kg
Max. number of users:	5
Fall zone: EN 1177	null, 30 m <sup>2</sup>
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 3

### Material

Wooden units - water-proof plywood  
 Metall parts - stainless steel  
 Plastic parts - HDPE  
 Slide - fibreglass

### Finish

null  
 null

### Description

The support structure of the slide is made from structural steel, which is zinc coated and KOMAXIT powder coated according to the RAL colour chart and is fixed in a concrete bed. All metal units are zinc coated and KOMAXIT powder coated according to the RAL colour chart.

The slide is made from fibreglass. The surface of the slide and side walls are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platform is made from water-proof plywood or from HDPE should the client require. All fastening material is galvanized or stainless steel.

