



UNIVERSAL 6U119KW - brown

Product type 6U-119KW-15

Basic information

Age category	3 - 15 years
Minimum area	8,5 m x 10,5 m
Equipment measurements	5,55 m x 5,85 m x 3,56 m
Free fall height:	1,5 m
Max. number of users:	10
Fall zone: EN 1177	null, 67 m ²
Availability of spare parts:	supplied by the
Certificate of Compliance:	

Material

Platform - HPL
 Metal units - structural steel
 Plastic units - HDPE
 Slide - fibreglass
 Climbing holds - mix of silica sand and epoxy resin

Finish


Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life, or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments).

The platform and the vertical climbing wall are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. All fastening material is galvanized or stainless steel.



Equipment

Tower, slide, roof, vertical climbing wall, ladder, metal beam, 3x barrier from HDPE.