



## UNIVERSAL 6U220KS - silver

Product type 6U-220KS-10

### Basic information

Age category	2 - 15 years
Minimum area	8,1 m x 8,6 m
Equipment measurements	5,13 m x 5,03 m x 3,06 m
Free fall height:	1, m
Load capacity:	702 kg
Max. number of users:	13
Fall zone: EN 1177	null
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Platform - HPL  
 Metal units - structural steel  
 Plastic units - HDPE  
 Slide - fibreglass  
 Ropes and nets - polypropylene with a steel internal core  
 Tunnel - fibreglass

### Finish

Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life, or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slide, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core). The platforms and the ramp are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). Crawl tunnel is made from fibreglass which is UV stable and it is characterised by high colour stability. All fastening material is galvanized or stainless steel.

### Equipment

2x tower, roof, slide, crawl tunnel between the towers, sloping ramp with the rope and HDPE steps, ladder, 5x barrier from HDPE.

