Playground » UNIVERSAL tower sets » Tower units with a platform higher than 1 m



www.zaidimuaiksteles-bonita.lt





UNIVERSAL 4U315KS - silver

4U-315KS-20 Product type

Basic information

3 - 15 years Age category Minimum area 14,5 m x 11 m

Equipment measurements 10,88 m x 7,07 m x 4,12 m

Free fall height: 2.0 m Max. number of users: 23

Fall zone: EN 1177 null, 118 m²

Certificate of Compliance: ČSN EN 1176-1 ed.2 +A1:2024

ČSN EN 1176-2 ed.2:2018 ČSN EN 1176-3 ed.2:2018 ČSN EN 1176-11:2015

Material

Platform - HPL Metal units - structural steel Plastic units - HDPE, polyamide Slides and tube slide - fibreglass

Ropes and nets - polypropylene with a steel internal core

Tunnel - fibreglass

Roofs - HPL

Finish

Duplex powder coated with coat curing Hot-dip galvanizing

14.5m 13m .07m 具 118m2 10.88m

Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide and tube slide are made from fibreglass. The surfaces of the slide, tube slide, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The climbing net, rope bridge are made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platforms and the ramp are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The crawler tunnel is made of fibreglass with high UV stability and high colour stability. The roofs are made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

Equipment

3x tower, slide, tube slide, 3x A-shaped roof, 6x barrier from HDPE, sloping ramp with the rope and HDPE steps, sloping ramp with steps and metal handles, crawl tunnel between the towers, rope bridge, metal beam, vertical climbing net.

We reserve the right to change products without prior notice, which will, from our point of view, improve quality. The pictures are only informative and the products shown may differ from the products that we currently supply. We also reserve the right to make printing errors and assume no responsibility for their possible consequences. Otherwise, our terms and conditions apply.

14.12.2025