Playground » Cableways





Single post cableway LD011K - galvanized

Product type

Basic information

| LD-011K20-10 |
|--------------|
| |

| Dasic information | | | | | |
|---|--|-----|----------|--------|--|
| Age category Minimum area Equipment measurements Free fall height: Load capacity: | 3 - 15 years 26,3 m x 4 m 24,04 m x 0,15 m x 3,78 m 1 m 130 kg | - * | | 26.3m | |
| Max. number of users: Fall zone: EN 1177 Designation: Availability of spare parts: Certificate of Compliance: | 2 null exterior supplied by the ČSN EN 1176 - 1 | C | _ | • | |
| Material | CSN EN 1170 - 1 | | < | 24.04m | |

Material

Metal units - structural steel Platforms - HPL Plastic units - HDPE

Finish

Hot-dip galvanizing

Description

The support structure are made from structural steel and is protected from corrosion by hot-dip galvanizing, which significantly prolongs the life of the play unit. The structure is fixed in a concrete bed. All other metal units are zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion The platform and the ramp are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). Steps are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). All fastening material is galvanized or stainless steel.