



# Twin chain swing with a slide RH6252KW - Brown (f.h. 1,5 m)

Product type

RH-6252KW-15

Basic	info	rmation
-------	------	---------


Age category	2 - 15 years
Minimum area	8,5 m x 8,5 m
Equipment measurements	5,32 m x 3,77 m x 2,32 m
Free fall height:	1,5 m
Load capacity:	324 kg
Max. number of users:	6
Fall zone: EN 1177	null, 52,5 m²
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

#### Material

Metal units - structural steel Platform - HPL Plastic units - HDPE Slide - fibreglass Seat Baby - rubber with an aluminum insert Seat Normal - aluminum, covered with a rubber

#### Finish

Duplex powder coated with coat curing Hot-dip galvanizing



52.5m2

## Description

The support structure of the swing is made from structural steel, which is zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion and is fixed in a concrete bed.

The slide is made from fibreglass. The surface of the slide is made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The swings are hung on a metal girder using galvanized chains. The platform is made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The Normal seat is made of aluminum, covered with a soft and comfortable rubber. The Baby seat baby is made of rubber and is reinforced with an aluminum insert. All fastening material is galvanized or stainless steel.

### Equipment

We offer three color variants of the support structure - red, blue and brown.

We reserve the right to change products without prior notice, which will, from our point of view, improve quality. The pictures are only informative and the products shown may differ from the products that we currently supply. We also reserve the right to make printing errors and assume no responsibility for their possible consequences. Otherwise, our terms and conditions apply.