



Agility hřiště AH-03

Product type AH-03

Basic information

Age category	0 - 0 years
Minimum area	19 m x 12 m
Equipment measurements	m x m x m
Free fall height:	m
Load capacity:	Not specified
Max. number of users:	Not specified
Fall zone: EN 1177	null
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	

Material

Metal parts - structural steel
Plastic parts - Foamlite
Tunnel - fiberglass

Finish

Duplex powder coated with coat curing
Hot-dip galvanizing

Description

The support structure is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements or duplex powder coated with coat curing according to RAL to prevent corrosion. These structures are embedded in a concrete base. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

All step boards are made of high quality Foamlite (high-pressure, which is characterised by high colour stability, UV resistance and mainly safety because it is rigid and there is no risk of injury caused by sharp broken fragments). Crawl tunnel is made from fibreglass which is UV stable and it is characterised by high colour stability. All connecting material is zinc or stainless steel coated.

Equipment

Climbing A, Beam, Swing, Jumper, Tunnel, Wall

