



## Skill path - brown

Product type SDO-8015KW-10

### Basic information

Age category	2 - 10 years
Minimum area	6,72 m x 5,72 m
Equipment measurements	3,72 m x 2,72 m x 1 m
Free fall height:	1 m
Max. number of users:	10
Fall zone: EN 1177	null
Certificate of Compliance:	ČSN EN 1176-1 ed.2 +A1:2024

### Material

Platform - HPL  
 Metal units - structural steel  
 Plastic units - HDPE, polyamide  
 Ropes and nets - polypropylene with a steel internal core  
 Tunnel - polyethylene

### Finish

Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The supporting structure is made of galvanized structural steel and then powder coated, and all other metal parts are made of black structural steel, sandblasted, duplex sprayed with powder coated. These structures are embedded in a concrete base. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. Ropes and nets are made of HERKULES (16 mm polypropylene ropes with inner steel core) and are connected by plastic connectors. The crawler tunnel is made of polyethylene with high UV stability and high colour stability. All step boards are made of high quality HDPE (high-pressure, full-coloured polyethylene, which is characterised by high colour stability, UV resistance and mainly safety because it is rigid and there is no risk of injury caused by sharp broken fragments). The platforms are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). All connecting material is zinc or stainless steel coated.

### Equipment

We offer two color variants of the support structure - brown and silver.