



Climbing set SS8409KS - silver

Product type SS-8409KS-20

Basic information

| | |
|------------------------------|---------------------------|
| Age category | 3 - 15 years |
| Minimum area | 5,5 m x 5,5 m |
| Equipment measurements | 1,3 m x 1,37 m x 2,12 m |
| Free fall height: | 2 m |
| Load capacity: | 216 kg |
| Max. number of users: | 4 |
| Fall zone: EN 1177 | null, 30,5 m ² |
| Designation: | exterior |
| Availability of spare parts: | supplied by the |
| Certificate of Compliance: | ČSN EN 1176 - 1 |

Material

Climbing wall - HPL
 Metal units - structural steel
 Climbing holds - mix of silica sand and epoxy resin

Finish

Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The support structure of the climbing set is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The climbing net is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and it is connected with plastic joints. The climbing wall is made from HPL (High-preSS88ure laminate, which is characterised by high colour stability, UV resistance and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. All fastening material is galvanized or stainless steel.

Equipment

Climbing wall, climbing pole, Swedish ladder, climbing net.

