Playground » UNIVERSAL tower sets » Tower units with a lower platform to 1 m



www.zaidimuaiksteles-bonita.lt





UNIVERSAL 4U118D

Product type 4U-118D-10

Basic information

Age category 2 - 15 years Minimum area 6,4 m x 4 m

Equipment measurements 2,98 m x 1,16 m x 3,13 m

Free fall height:

Load capacity:

Max. number of users:

Fall zone: EN 1177

Designation:

Availability of spare parts:

Certificate of Compliance:

1 m
270 kg
5 null
exterior
supplied by the
ČSN EN 1176 - 1, 2, 3

Material

Roof - HPL

Wooden units - thick glued wooden supports Metal units - structural steel Plastic units - HDPE Slide - fibreglass

Finish

null

Duplex powder coated with coat curing Hot-dip galvanizing

Description

6.4m 2.98m

The tower unit support structure is made from thick glued wooden supports. This solution ensures maximum protection against cracking, which is common for products made from solid wood. The wooden supports are impregnated and coated with a triple layer of lacquer, which meets the terms and conditions of the EN71/3 Standard (safe for children's toys). The structures are anchored into the ground in steel plates, which are protected against corrosion by hot-dip galvanizing and fixed in a concrete bed. The anchors are fastened to the play unit with bolts and their structure ensures that they are not in direct contact with the ground. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platform is made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The roof is made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

Equipment

Tower, slide, A-shaped roof, 2x barrier, ladder.