Category

Playground » UNIVERSAL tower sets » Tower units with a lower platform to 1 m



www.zaidimuaiksteles-bonita.lt



UNIVERSAL 6U306KW - brown

6U-306KW-10

Product type

Basic information

Age category Minimum area Equipment measurements Free fall height: Load capacity: Max. number of users: Fall zone: EN 1177 Designation: Availability of spare parts: Certificate of Compliance:	2 - 15 years 11,4 m x 9,9 m 8,24 m x 6,24 m x 3,06 m 1 m 1188 kg 22 null exterior supplied by the ČSN EN 1176 - 1, 2, 3
Certificate of Compliance:	CSN EN 1176 - 1, 2, 3

Material

Platform - HPL Metal units - stainless steel Ropes and nets - polypropylene with a steel internal core Plastic units - HDPE, polyamide Slide - fibreglass Tunnel - fibreglass Climbing holds - mix of silica sand and epoxy resin

Finish

Duplex powder coated with coat curing Hot-dip galvanizing

Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life, or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope bridge is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and is connected with plastic or aluminium joints. The platforms and the sloping climbing wall are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. The crawler tunnel is made of laminate. All fastening material is galvanized or stainless steel.

Equipment

3x tower, slide, roof, sloping climbing wall, rope bridge, ladder, crawl tunnel between the towers, fire pole, metal beam, 6x barrier from HDPE.

We reserve the right to change products without prior notice, which will, from our point of view, improve quality. The pictures are only informative and the products shown may differ from the products that we currently supply. We also reserve the right to make printing errors and assume no responsibility for their possible consequences. Otherwise, our terms and conditions apply. 17.05.2025

