Playground » Playground accessories





Double panel drawing board TK200KS - silver

Product type

TK-200KS-10

Basic information

| | | 4 | | | |
|---|--------------------------------|------|--------------|---|---|
| Age category | from 0 years | - | | | |
| Minimum area | 5,4 m x 3,1 m | F | 7 | | - |
| Equipment measurements | 2,4 m x 0,08 m x 1,41 m | | | | |
| Free fall height: | 0 m | | | | |
| Load capacity: Max. number of users: | Not specified Not specified | F | • | | |
| Fall zone: EN 1177 | null | | | | |
| Designation: | exterior | | | | - |
| Availability of spare parts: | supplied by the | 1 | 5.4m | | |
| Certificate of Compliance: | ČSN EN 1176 - 1 | * | | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | |
| Material | | | | | |
| Metal parts - structural steel | I | - | | 1 | |
| Wooden parts - water-proof plywood | | | | / | |
| | | (BB | |) | |
| | | Ö | | | |
| | | 1 | | _ | |
| | | Į 1 | 2.4m | | |
| | | | 2.4111 | -> / | |

Finish

Duplex powder coated with coat curing Hot-dip galvanizing

Description

The support structure of the drawing board is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements or duplex powder coated with coat curing according to RAL to prevent corrosion. These structures are anchored to concrete footings. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The drawing area is made from water-proof plywood, which is designed for external use. All fastening material is galvanized or stainless steel.