# Playground » UNIVERSAL tower sets » Tower units with a platform higher than 1 m



www.zaidimuaiksteles-bonita.lt



## UNIVERSAL 4U308KW - brown

Product type 4U-308KW-15

#### **Basic information**

Age category 3 - 15 years 10 m x 8,5 m Minimum area

**Equipment measurements** 6,6 m x 4,9 m x 3,17 m

1.5 m Free fall height: Not specified Load capacity: Max. number of users: Not specified Fall zone: EN 1177 null, 61 m<sup>2</sup>

Designation: exterior supplied by the Availability of spare parts: Certificate of Compliance: ČSN EN 1176 - 1, 2, 3

#### Material

Platform - HPL

Metal units - structural steel Plastic units - HDPE, polyamide

Slide - fibreglass


Ropes and nets - polypropylene with a steel internal core Climbing holds - mix of silica sand and epoxy resin

Tunnel - fibreglass

#### **Finish**

Duplex powder coated with coat curing

# Hot-dip galvanizing



#### **Description**

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The climbing net and the rope are made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platforms, ramp and the sloping climbing wall are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. The crawler tunnel is made of fibreglass with high UV stability and high colour stability. All fastening material is galvanized or stainless steel.

### **Equipment**

3x tower, slide, 3x barrier made from HDPE, crawl tunnel between the towers, sloping net access, sloping ramp with the rope and HDPE steps, sloping climbing wall, sloping ramp with steps and metal handles.

We reserve the right to change products without prior notice, which will, from our point of view, improve quality. The pictures are only informative and the products shown may differ from the products that we currently supply. We also reserve the right to make printing errors and assume no responsibility for their possible consequences. Otherwise, our terms and conditions apply.