



## UNIVERSAL 4U413K-B

Product type 4U-413KY-10-B

### Basic information

Age category	0 - 10 years
Minimum area	6,3 m x 5,5 m
Equipment measurements	3,3 m x 2,5 m x 1,7 m
Free fall height:	1 m
Load capacity:	540 kg
Max. number of users:	10
Fall zone: EN 1177	null
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Plastic parts - PE  
 Metal parts - aluminum profiles  
 Aperture - plexiglass  
 Tunnel - PE

### Finish

Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The supporting structure of the tower set is made of aluminum profiles (profile 80 x 80 mm) and coating with baked paint KOMAXIT according to the RAL colour system. These structures are fixed in a concrete bed. Barriers, tunnel, roofs and platforms are made of high quality plastic PE (polyethylene, which is characterized by high color fastness, resistance to UV radiation and mainly safety, because it is non-breakable and there is no risk of injury to children sharp fragments). All fasteners are stainless.

### Equipment

2x Tower, 2x roof, 2x barrier with an aperture, 6x barrier, tunnel