



UNIVERSAL 4U204KS-Q - silver (Coastal region)

Product type 4U-204KS-15-Q

Basic information

Age category	3 - 15 years
Minimum area	6,5 m x 7 m
Equipment measurements	3,36 m x 3,58 m x 3,63 m
Free fall height:	1,5 m
Load capacity:	432 kg
Max. number of users:	8
Fall zone: EN 1177	null, 38 m ²
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

Material

Platforms, roof, drawing board - HPL
 Metal units - structural steel
 Plastic units - HDPE, polyamide
 Slide - fibreglass

Finish

Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The support structure of the tower unit is made of structural steel (metal profile 100 × 100 mm) which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platform, roof and the drawing board are made from HPL (High-pressure laminate). All fastening material is galvanized or stainless steel.

Equipment

2x tower, slide, A-shaped roof, drawing board, sloping ramp with steps and metal handles, 4x barrier from HDPE, abacus.

