



UNIVERSAL 6U236D

Product type 6U-236D-15

Basic information

Age category	3 - 15 years
Minimum area	11 m x 10,5 m
Equipment measurements	7,72 m x 5,63 m x 3,56 m
Free fall height:	1,5 m
Load capacity:	702 kg
Max. number of users:	13
Fall zone: EN 1177	null, 84,5 m ²
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

Material

Wooden units - thick glued wooden supports
 Metal units - structural steel
 Plastic units - HDPE
 Slide - fibreglass
 Tunnel - fibreglass

Finish

null
 Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The tower unit support structure is made from thick glued wooden supports. This solution ensures maximum protection against cracking, which is common for products made from solid wood. The wooden supports are impregnated and coated with a triple layer of lacquer, which meets the terms and conditions of the EN71/3 Standard (safe for children's toys). The structures are anchored into the ground in steel plates, which are protected against corrosion by hot-dip galvanizing and fixed in a concrete bed. The anchors are fastened to the play unit with bolts and their structure ensures that they are not in direct contact with the ground. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. The slide is made from fibreglass. The surfaces of the slide, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platforms are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). Crawl tunnel is made from fibreglass which is UV stable and it is characterised by high colour stability. All fastening material is galvanized or stainless steel.

Equipment

2x tower, roof, slide, crawl tunnel between the towers, 2x ladder, metal beam, 5x barrier from HDPE.

